



US 6,117,700A

United States Patent [19]

Orita et al.

[11] Patent Number: 6,117,700

[45] Date of Patent: Sep. 12, 2000

[54] METHOD FOR FABRICATING
SEMICONDUCTOR DEVICE HAVING
GROUP III NITRIDE[75] Inventors: Kenji Orita; Masahiro Ishida; Shinji
Nakamura; Masaaki Yuri, all of
Osaka, Japan[73] Assignee: Matsushita Electronics Corporation,
Osaka, Japan

[21] Appl. No.: 09/389,024

[22] Filed: Sep. 2, 1999

[30] Foreign Application Priority Data

Sep. 9, 1998	[JP]	Japan	10-254996
Nov. 17, 1998	[JP]	Japan	10-326352

[51] Int. Cl.⁷ H01L 21/00[52] U.S. Cl. 438/46; 438/22; 438/513;
438/688; 438/796[58] Field of Search 438/22, 46, 513,
438/688, 796

[56] References Cited

U.S. PATENT DOCUMENTS

5,874,320 2/1999 Shih et al. .

FOREIGN PATENT DOCUMENTS

58-100471	6/1983	Japan .
6-9258	2/1994	Japan .
6-275868	9/1994	Japan .
6-350137	12/1994	Japan .
8-213656	8/1996	Japan .
10-144960	5/1998	Japan .
10-163529	6/1998	Japan .



Primary Examiner—Long Pham

Attorney, Agent, or Firm—Eric J. Robinson; Nixon Peabody
LLP

[57] ABSTRACT

First, n-type contact layer of GaN, n-type cladding layer of AlGaIn, active layer of InGaIn, first Mg-doped layer of AlGaIn and second Mg-doped layer of GaN are grown in this order over a sapphire substrate. Thereafter, the substrate, including the second Mg-doped layer, is exposed to nitrogen plasma for about 40 minutes. As a result, Mg, which has been introduced into the first and second Mg-doped layers, is activated as an acceptor. Thus, p-type cladding layer and p-type contact layer with low resistance and excellent crystallinity can be formed out of the first and second Mg-doped layers, respectively.

15 Claims, 9 Drawing Sheets



BEST AVAILABLE COPY

09986997 111301